



W1 - Poetsdoeken
muur/vloer/standaard systeem

Tork Cleaning Cloth Roll (Wit)



Artikel	510104
Rollengte	380 m
Systeem	W1 - Poetsdoeken muur/vloer/standaard systeem
Rolbreedte	42.8 cm
Roldiameter	38 cm
Aantal vellen	1000
Vellengte	38 cm
Binnenste diameter van kern	7.3 cm
Lagen	1
Kleur	Wit

- exelCLEAN™ voor meer efficiëntie bij het schoonmaken
- Multifunctioneel – de meeste oppervlakken in een veeg schoon
- Zacht en flexibel – ideaal in nauwe ruimtes
- Goedgekeurd voor gebruik met voedingsmiddelen
- Tork Easy Handling™, verpakking is makkelijk te dragen, te openen, in te vouwen en af te voeren



www.tork.be

Verzendgegevens			
	Consumentenverpakking	Colli (trp)	Pallet
EAN	7322540057256	7322540057256	7322540275650
Aantal	1	1	30
Consumentenverpakkingen	-	1	30
Hoogte	443 mm	443 mm	2365 mm
Breedte	396 mm	396 mm	800 mm
Lengte	396 mm	396 mm	1200 mm
Inhoud (ml)	69.5 dm3	69.5 dm3	2.1 m3
Nettogewicht	8945 g	8.9 kg	268.36 kg
Totaalgewicht	9708 g	9.7 kg	291.24 kg
Verpakkingsmateriaal	-	Carton	-

Milieu-informatie	
Content	Chemical pulp, Polypropene, Polyester, Chemicals
Material	Chemical pulpChemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone.ECF is used in this product. PolypropenePolypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength. PolyesterPolyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.Chemicals Both functional and process chemicals are used. The functional chemical used is wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre. Process chemical used is a surfactant.
Production	This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.
Destruction	This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.

Kies een dispenser



Alternatieve producten



Productcertificaten



Contact

SCA Hygiene Products Belgium NV/SA
Culliganlaan 1D
1831 DIEGEM
België

Tel no: 02/766 05 30
Fax: 00800 9574 2540
E-mail: info@tork.be